

---

## General Solution of Poisson Equation for Plane Wall, Long Solid Circular Cylinder and Solid Sphere

---

The general Poisson equation  $\nabla^2 T = -\mathcal{P}/k$  with appropriate boundary conditions, and the general solution which is valid for the plane wall, long solid circular cylinder and solid sphere is presented below. The temperature is one-dimensional, ie  $T = T(u)$  where  $u$  represents the  $x$ - and  $r$ - coordinates in the plane wall, cylinder and sphere. The distributed volumetric heat sources  $\mathcal{P}$  and the thermal conductivity  $k$  are constant.

### Differential Equation

$$\frac{1}{u^n} \frac{d}{du} \left( u^n \frac{dT}{du} \right) = -\frac{\mathcal{P}}{k}, \quad 0 \leq u \leq b, \quad n = 0, 1, 2$$

### Boundary Conditions

$$u = 0, \quad \frac{dT}{du} = 0, \quad \text{symmetry condition}$$

$$u = b, \quad \frac{dT}{du} = -\frac{h}{k} [T(b) - T_f]$$

The parameters in the previous equations are defined below for the three geometries.

Geometry	Plane Wall	Cylinder	Sphere
$u =$	$x$	$r$	$r$
$b =$	$L$	$b$	$b$
$n =$	$0$	$1$	$2$

### Solution

Integrating once gives the temperature gradient:

$$\frac{dT}{du} = -\frac{\mathcal{P}}{k} \frac{u}{n+1} + \frac{C_1}{u^n}$$

with the first integration constant  $C_1$ .

The second integration gives the temperature distribution:

$$T(u) = -\frac{\mathcal{P}}{k} \frac{u^2}{2(n+1)} + C_1 \frac{u^{1-n}}{(1-n)} + C_2$$

with the second integration constant  $C_2$ .

To satisfy the symmetry condition at  $u = 0$ , the first integration constant must be set to zero, i.e.,  $C_1 = 0$ . The second boundary condition leads to the relation:

$$-\frac{\mathcal{P}b}{k(n+1)} = -\frac{h}{k} \left[ -\frac{\mathcal{P}b^2}{2k(n+1)} + C_2 - T_f \right]$$

The previous relation gives the second constant of integration:

$$C_2 = T_f + \frac{\mathcal{P}b}{h(n+1)} + \frac{\mathcal{P}b^2}{2k(n+1)}$$

### General Temperature Distribution

The general temperature distribution can be written as

$$T(u) - T_f = \frac{\mathcal{P}}{2k(n+1)}(b^2 - u^2) + \frac{\mathcal{P}b}{h(n+1)}, \quad 0 \leq u \leq b$$

which is valid for  $n = 0$  (plane wall),  $n = 1$  (long solid cylinder), and  $n = 2$  (solid sphere).

### Wall or Surface Temperature Drop

The temperature drop from the wall (or surface) to the fluid is obtained from the general solution by setting  $u = b$  and  $T(b) = T_s$ . Therefore we get

$$T_s - T_f = \frac{\mathcal{P}b}{h(n+1)}$$

### Centerline or Axis Temperature Drop

The temperature drop from the centerline or the axis where the maximum temperature occurs to the fluid is obtained from the general solution by setting  $u = 0$  and  $T(0) = T_{\max}$ . Therefore we get

$$T_{\max} - T_f = \frac{\mathcal{P}b^2}{2k(n+1)} + \frac{\mathcal{P}b}{h(n+1)}$$

### Solid Temperature Drop

The temperature drop across the solid is

$$T_{\max} - T_s = \frac{\mathcal{P}b^2}{2k(n+1)}$$

## Ratio of Solid to Film Temperature Drops

The ratio of the solid temperature drop to the film temperature drop is obtained from

$$\frac{\Delta T_{\text{solid}}}{\Delta T_{\text{film}}} = \frac{T_{\text{max}} - T_s}{T_s - T_f} = \frac{1}{2} \frac{hb}{k} = \frac{1}{2} Bi$$

where  $Bi$  is the Biot number.